



Den Braven

Aluband

Strong self adhesive flashing



PRODUCT DESCRIPTION

Zwaluw Aluband is a strong self adhesive flashing of a modified bituminous layer with a top cover of strong weather resistant, aluminium or lead coloured polyester foil, and an easily removable siliconised high density polyethylene release foil underneath.

KEY BENEFITS

- Adheres well to almost all substrates
- Paintable
- Available in multiple sizes
- UV-resistant

APPLICATIONS

Zwaluw Aluband can be used for flashing gutters, bay windows, between walls and extensions. Zwaluw Aluband instantly bonds to many surfaces. It is easily applied in the desired shape. The foil is weather resistant and has a high tear resistance.

DIRECTION FOR USE

General rule is to add 100mm to the joint width, 50mm for both sides. Minimum overlap between Zwaluw Aluband strips is at least 25 mm. For a complete overview see our website or contact Den Braven.

TECHNICAL SPECIFICATIONS

Application Temperature	0°C to +35°C
Density	1,40 g/m ²
Frost Resistance	Up to -15°C
Temperature Resistance	-40°C to +80°C

These are typical values

LIMITATIONS

Not suitable for PE, PP, PC, PMMA and PTFE

SURFACE PREPARATIONS AND FINISHING

Before using the Zwaluw Aluband refer to the Health & Safety Sheet. All surfaces must be clean, dry and free of dust, grease and other loose material. Adhesion tests prior to application are recommended. Thoroughly clean by using Zwaluw Cleaner and two cloths. Porous surfaces should be primed with Zwaluw B&B Primer Universal or Zwaluw B&B Spray Primer Universal. Contact Den Braven for a full recommendation.

Clean the surfaces thoroughly by using Zwaluw Cleaner. If necessary use a primer.

CLEANING

Surfaces, material and tools can be cleaned by using Zwaluw Cleaner.

SHELF LIFE

Storage between +5°C and +25°C and in shaded conditions. Shelf life is 36 months when stored as recommended in original unopened packaging.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.